

SERIE G-GP.32

PROFESSIONAL

- Manual feed (serie G.32) and automatic feed (serie GP.32)
- Geared drive
- Displaceable table and fixed headstock



Standard equipment

- Adjustable depth end
- Tool ejector
- Emergency push button
- Turning sense selector
- Electrical equipment at low voltage
- Drill guard with stop micro
- CE norms



Extra Equipment

20010 Lighting equipment

91118 Coolant equipment

20082 Rotating table (serie G.32 and GP.32)

20042 Tapping system IR/RS

SANDFELD [®]
AS
VÆRKTØJSMASKINER

Birkegårdsvej 2 · 7400 Herning · Denmark · Phone +45 97 11 92 22 · www.sandfeld.com

Characteristics

G.32

GP.32

DRILLING CAPACITY IN STEEL OF 70 Kg. (mm)	32	
TAPPING CAPACITY IN STEEL OF 70 Kg.	M24	
TRANSMISSION	GEARS (Hardened and ground)	
SPEED NUMBER AND RANGE	65-125-185-365-540-1055-1560-3060 rpm.	
FEED	MANUAL	AUTOMATIC
NUMBER AND RANGE OF FEEDS	-	(3) 0,10-0,20-0,30
CLUTCH	-	MECHANIC
MAIN MOTOR POWER - 750/1500 rpm.	2,5/3,5 HP	
SPINDLE CONE	MT3	
SPINDLE STROKE	120 mm	
DISTANCE SPINDLE-COLUMN	250 mm	
DISTANCE SPINDLE-TABLE	Min. 85 mm/ Max. 635 mm	
DISTANCE SPINDLE-BASE	1170 mm	
COLUMN DIAMETER	Ø100 mm	
DIMENSIONS OF THE TABLE (WITH 2 T SLOTS)	270x300 mm	
DIMENSIONS OF THE BASE WITHOUT T SLOTS (WITHOUT COOLANT)	600x380 mm	
DIMENSIONS OF THE BASE WITH T SLOTS (WITH COOLANT)	665x400 mm	
WEIGHT: NET / GROSS Kg.	260 / 320 Kg.	
PACKAGING DIMENSIONS AND VOLUME	2110x570x800 mm / 0,97m ³	2140x600x800 / 1,02 m ³

Dimensions

